

High Performance Cable Assemblies

Johnson offers microwave and millimeter wave frequency cable assemblies which offer superior mechanical and electrical performance, excellent return loss and phase stability. They are designed using low-loss, ultra low-loss flexible and semi-rigid cable types.

Cable assemblies are available in straight and right-angle configurations in the following families: 2.92 mm, 2.4 mm, 1.85 mm and SMPM, SMP, and SMAs. Johnson prides itself on building standard and custom products to meet our customers requirements.

Features


- Excellent operating performance up to 67 GHz
- VSWR range from 1.30 to 1.50
- Vp, Velocity of Propagation from 74% to 76%

Applications

- Test and Measurement
- Wireless and Radar Systems
- Satellite and Defense systems
- Networking Equipment



1.85 mm Straight Plug to 1.85 mm Straight Plug (67 GHz)




Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB)		VSWR (Max)
						20 GHz	67 GHz	
415-0537-MM100	-	100 mm	Flexible	0.096 in	+4 mm / -0.0 mm	<-0.7 dB	<-1.2 dB	1.30
415-0537-006	6 in	-	Flexible	0.096 in	+0.157 in / -0.0 in	<-0.8 dB	<-1.5 dB	1.30
415-0537-MM200	-	200 mm	Flexible	0.096 in	+5 mm / -0.0 mm	<-1.1 dB	<-1.9 dB	1.30
415-0537-012	12 in	-	Flexible	0.096 in	+0.196 in / -0.0 in	<-1.5 dB	<-2.4 dB	1.30
415-0537-018	18 in	-	Flexible	0.096 in	+0.314 in / -0.0 in	<-2.1 dB	<-3.3 dB	1.30
415-0537-MM500	-	500 mm	Flexible	0.096 in	+10 mm / -0.0 mm	<-2.3 dB	<-3.6 dB	1.30
415-0537-024	24 in	-	Flexible	0.096 in	+0.393 in / -0.0 in	<-2.8 dB	<-4.0 dB	1.30
415-0537-036	36 in	-	Flexible	0.096 in	+0.590 in / -0.0 in	<-3.5 dB	<-6.1 dB	1.30
415-0537-M1.0	-	1000 mm	Flexible	0.096 in	+15 mm / -0.0 mm	<-3.7 dB	<-6.6 dB	1.30

High Performance Cable Assemblies

Johnson


Flexible

2.4 mm Straight Plug to 2.4 mm Straight Plug (50 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB)		VSWR (Max)
						20 GHz	50 GHz	
415-0536-MM100	-	100 mm	Flexible	0.096 in	+4 mm / -0.0 mm	<-0.6 dB	<-1.0 dB	1.30
415-0536-006	6 in	-	Flexible	0.096 in	+0.157 in / -0.0 in	<-0.7 dB	<-1.2 dB	1.30
415-0536-MM200	-	200 mm	Flexible	0.096 in	+5 mm / -0.0 mm	<-1.0 dB	<-1.6 dB	1.30
415-0536-012	12 in	-	Flexible	0.096 in	+0.196 in / -0.0 in	<-1.4 dB	<-2.0 dB	1.30
415-0536-018	18 in	-	Flexible	0.096 in	+0.314 in / -0.0 in	<-2.0 dB	<-2.7 dB	1.30
415-0536-MM500	-	500 mm	Flexible	0.096 in	+10 mm / -0.0 mm	<-2.2 dB	<-3.1 dB	1.30
415-0536-024	24 in	-	Flexible	0.096 in	+0.393 in / -0.0 in	<-2.7 dB	<-3.5 dB	1.30
415-0536-036	36 in	-	Flexible	0.096 in	+0.590 in / -0.0 in	<-3.3 dB	<-5.0 dB	1.30
415-0536-M1.0	-	1000 mm	Flexible	0.096 in	+15 mm / -0.0 mm	<-3.6 dB	<-5.5 dB	1.30

SMP Straight Female to 2.4 mm Straight Plug (40 GHz)




Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB)		VSWR (Max)
						40 GHz	40 GHz	
415-0543-MM100	-	100 mm	Flexible	0.047 in	+4 mm / -0.0 mm	<-2.3 dB		1.33
415-0543-006	6 in	-	Flexible	0.047 in	+0.157 in / -0.0 in	<-2.5 dB		1.33
415-0543-MM200	-	200 mm	Flexible	0.047 in	+5 mm / -0.0 mm	<-3.4 dB		1.33
415-0543-012	12 in	-	Flexible	0.047 in	+0.196 in / -0.0 in	<-4.1 dB		1.33
415-0543-018	18 in	-	Flexible	0.047 in	+0.314 in / -0.0 in	<-5.8 dB		1.33
415-0543-MM500	-	500 mm	Flexible	0.047 in	+10 mm / -0.0 mm	<-6.5 dB		1.33
415-0543-024	24 in	-	Flexible	0.047 in	+0.393 in / -0.0 in	<-7.3 dB		1.33
415-0543-036	36 in	-	Flexible	0.047 in	+0.590 in / -0.0 in	<-10.6 dB		1.33
415-0543-M1.0	-	1000 mm	Flexible	0.047 in	+15 mm / -0.0 mm	<-11.2 dB		1.33

High Performance Cable Assemblies

Johnson


Flexible

SMPM Straight Female to 2.4 mm Straight Plug (50 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB)		VSWR (Max)
						50 GHz	50 GHz	50 GHz
415-0545-MM100	-	100 mm	Flexible	0.047 in	+4 mm / -0.0 mm	<-2.4dB		1.5
415-0545-006	6 in	-	Flexible	0.047 in	+0.157 in / -0.0 in	<-2.6dB		1.5
415-0545-MM200	-	200 mm	Flexible	0.047 in	+5 mm / -0.0 mm	<-3.5dB		1.5
415-0545-012	12 in	-	Flexible	0.047 in	+0.196 in / -0.0 in	<-4.2 dB		1.5
415-0545-018	18 in	-	Flexible	0.047 in	+0.314 in / -0.0 in	<-5.9 dB		1.5
415-0545-MM500		500 mm	Flexible	0.047 in	+10 mm / -0.0 mm	<-6.6dB		1.5
415-0545-024	24 in	-	Flexible	0.047 in	+0.393 in / -0.0 in	<-7.4 dB		1.5
415-0545-036	36 in	-	Flexible	0.047 in	+0.590 in / -0.0 in	<-10.7 dB		1.5
415-0545-M1.0	-	1000 mm	Flexible	0.047 in	+15 mm / -0.0 mm	<-11.4dB		1.5

2.92 mm Straight Plug to 2.92 mm Straight Plug (40 GHz)




Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB)		VSWR (Max)
						20 GHz	40 GHz	40 GHz
415-0210-MM100	-	100 mm	Flexible	0.160 in (HP160S)	+4 mm / -0.0 mm	<-0.98dB	<-1.69dB	1.25
415-0210-006	6 in	-	Flexible	0.160 in (HP160S)	+0.157 in / -0.0 mm	<-0.77dB	<-1.37dB	1.25
415-0210-MM200	-	200 mm	Flexible	0.160 in (HP160S)	+5 mm / -0.0 mm	<-1.53dB	<-2.50dB	1.25
415-0210-012	12 in	-	Flexible	0.160 in (HP160S)	+0.197 in / -0.0 in	<-1.10dB	<-1.87dB	1.25
415-0210-018	18 in	-	Flexible	0.160 in (HP160S)	+0.315 in / -0.0 in	<-1.44dB	<-2.36dB	1.25
415-0210-MM500		500mm	Flexible	0.160 in (HP160S)	+10 mm / -0.0 mm	<-1.53dB	<-2.50dB	1.25
415-0210-024	24 in	-	Flexible	0.160 in (HP160S)	+0.590 in / -0.0 in	<-1.77dB	<-2.86dB	1.25
415-0210-MM750		750mm	Flexible	0.160 in (HP160S)	+15 mm / -0.0 mm	<-2.07dB	<-3.31dB	1.25
415-0210-036	36 in	-	Flexible	0.160 in (HP160S)	+1.18 in / -0.0 in	<-2.43dB	<-3.85dB	1.25
415-0210-M1.0	-	1000 mm	Flexible	0.160 in (HP160S)	+30 mm / -0.0 mm	<-2.62dB	<-4.12dB	1.25

High Performance Cable Assemblies

Johnson


Flexible

SMP Straight Female to 2.92 mm Straight Plug (40 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB) 40 GHz	VSWR (Max) 40 GHz
415-0542-MM100	-	100 mm	Flexible	0.047 in	+4 mm / -0.0 mm	<-2.3 dB	1.33
415-0542-006	6 in	-	Flexible	0.047 in	+0.157 in / -0.0 in	<-2.5 dB	1.33
415-0542-MM2200	-	200 mm	Flexible	0.047 in	+5 mm / -0.0 mm	<-3.2 dB	1.33
415-0542-012	12 in	-	Flexible	0.047 in	+0.196 in / -0.0 in	<-3.8 dB	1.33
415-0542-018	18 in	-	Flexible	0.047 in	+0.314 in / -0.0 in	<-5.1 dB	1.33
415-0542-MM500		500 mm	Flexible	0.047 in	+10 mm / -0.0 mm	<-5.5 dB	1.33
415-0542-024	24 in	-	Flexible	0.047 in	+0.393 in / -0.0 in	<-6.5 dB	1.33
415-0542-036	36 in	-	Flexible	0.047 in	+0.590 in / -0.0 in	<-9.2 dB	1.33
415-0542-M1.0	-	1000 mm	Flexible	0.047 in	+15 mm / -0.0 mm	<-9.9 dB	1.33

SMPM Straight Female to 2.92 mm Straight Plug (40 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	Insertion Loss (Max dB) 40 GHz	VSWR (Max) 40 GHz
415-0544-MM100	-	100 mm	Flexible	0.047 in	+4 mm / -0.0 mm	<-2.4dB	1.4
415-0544-006	6 in	-	Flexible	0.047 in	+0.157 in / -0.0 in	<-2.6dB	1.4
415-0544-MM200	-	200 mm	Flexible	0.047 in	+5 mm / -0.0 mm	<-3.3 dB	1.4
415-0544-012	12 in	-	Flexible	0.047 in	+0.196 in / -0.0 in	<-3.8 dB	1.4
415-0544-018	18 in	-	Flexible	0.047 in	+0.314 in / -0.0 in	<-5.1 dB	1.4
415-0544-MM500		500 mm	Flexible	0.047 in	+10 mm / -0.0 mm	<-5.7 dB	1.4
415-0544-024	24 in	-	Flexible	0.047 in	+0.393 in / -0.0 in	<-6.6 dB	1.4
415-0544-036	36 in	-	Flexible	0.047 in	+0.590 in / -0.0 mm	<-9.3 dB	1.4
415-0544-M1.0	-	1000 mm	Flexible	0.047 in	+30 mm / -0.0 mm	<-10.0 dB	1.4




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Flexible


Johnson

SMPM Straight Female to SMPM Straight Female (40 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 40 GHz
415-0527-006	6 in	-	Flexible	0.086 in	±0.15 in	1.50
415-0527-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.50
415-0527-MM250	-	250 mm	Flexible	0.086 in	±6 mm	1.50
415-0527-012	12 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0527-018	18 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0527-MM500	-	500 mm	Flexible	0.086 in	±6 mm	1.50
415-0527-024	24 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0527-036	36 in	-	Flexible	0.086 in	±0.50 in	1.50
415-0527-M1.0	-	1000 mm	Flexible	0.086 in	±12 mm	1.50

SMPM Straight Female to SMPM Straight Female (40 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 40 GHz
415-0533-006	6 in	-	Flexible	0.047 in	±0.15 in	1.50
415-0533-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.50
415-0533-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.50
415-0533-012	12 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0533-018	18 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0533-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.50
415-0533-024	24 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0533-036	36 in	-	Flexible	0.047 in	±0.50 in	1.50
415-0533-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Flexible


Johnson

SMPM Straight Female to SMPM Right Angle Female (30 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 30 GHz
415-0528-006	6 in	-	Flexible	0.086 in	±0.15 in	1.50
415-0528-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.50
415-0528-MM250	-	250 mm	Flexible	0.086 in	±6 mm	1.50
415-0528-012	12 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0528-018	18 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0528-MM500	-	500 mm	Flexible	0.086 in	±6 mm	1.50
415-0528-024	24 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0528-036	36 in	-	Flexible	0.086 in	±0.50 in	1.50
415-0528-M1.0	-	1000 mm	Flexible	0.086 in	±12 mm	1.50

SMPM Straight Female to SMPM Right Angle Female (20 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 20 GHz
415-0534-006	6 in	-	Flexible	0.047 in	±0.15 in	1.30
415-0534-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.30
415-0534-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.30
415-0534-012	12 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0534-018	18 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0534-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.30
415-0534-024	24 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0534-036	36 in	-	Flexible	0.047 in	±0.50 in	1.30
415-0534-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.30




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Flexible


Johnson

SMPM Right Angle Female to SMPM Right Angle Female (30 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 30 GHz
415-0529-006	6 in	-	Flexible	0.047 in	±0.15 in	1.50
415-0529-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.50
415-0529-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.50
415-0529-012	12 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0529-018	18 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0529-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.50
415-0529-024	24 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0529-036	36 in	-	Flexible	0.047 in	±0.50 in	1.50
415-0529-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.50

SMPM Right Angle Female to SMPM Right Angle Female (20 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 20 GHz
415-0535-006	6 in	-	Flexible	0.047 in	±0.15 in	1.30
415-0535-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.30
415-0535-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.30
415-0535-012	12 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0535-018	18 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0535-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.30
415-0535-024	24 in	-	Flexible	0.047 in	±0.25 in	1.30
415-0535-036	36 in	-	Flexible	0.047 in	±0.50 in	1.30
415-0535-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.30




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson


Flexible

SMP Straight Female to SMP Straight Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0503-MM100	-	100 mm	Flexible	0.086 in	±6 mm	1.50
415-0503-006	6 in	-	Flexible	0.086 in	±0.15 in	1.50
415-0503-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.50
415-0503-MM250	-	250 mm	Flexible	0.086 in	±6 mm	1.50
415-0503-012	12 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0503-018	18 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0503-MM500	-	500 mm	Flexible	0.086 in	±6 mm	1.50
415-0503-024	24 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0503-036	36 in	-	Flexible	0.086 in	±0.50 in	1.50
415-0503-M1.0	-	1000 mm	Flexible	0.086 in	±12 mm	1.50

SMP Straight Female to SMP Straight Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0509-MM100	-	100 mm	Flexible	0.047 in	±6 mm	1.50
415-0509-006	6 in	-	Flexible	0.047 in	±0.15 in	1.50
415-0509-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.50
415-0509-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.50
415-0509-012	12 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0509-018	18 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0509-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.50
415-0509-024	24 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0509-036	36 in	-	Flexible	0.047 in	±0.50 in	1.50
415-0509-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson

Flexible

SMP Straight Female to SMP Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0504-006	6 in	-	Flexible	0.086 in	±0.15 in	1.50
415-0504-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.50
415-0504-MM250	-	250 mm	Flexible	0.086 in	±6 mm	1.50
415-0504-012	12 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0504-018	18 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0504-MM500	-	500 mm	Flexible	0.086 in	±6 mm	1.50
415-0504-024	24 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0504-036	36 in	-	Flexible	0.086 in	±0.50 in	1.50
415-0504-M1.0	-	1000 mm	Flexible	0.086 in	±12 mm	1.50

SMP Straight Female to SMP Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0510-006	6 in	-	Flexible	0.047 in	±0.15 in	1.50
415-0510-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.50
415-0510-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.50
415-0510-012	12 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0510-018	18 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0510-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.50
415-0510-024	24 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0510-036	36 in	-	Flexible	0.047 in	±0.50 in	1.50
415-0510-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson


Flexible

SMP Right Angle Female to SMP Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0505-MM100	-	100 mm	Flexible	0.086 in	±6 mm	1.50
415-0505-006	6 in	-	Flexible	0.086 in	±0.15 in	1.50
415-0505-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.50
415-0505-MM250	-	250 mm	Flexible	0.086 in	±6 mm	1.50
415-0505-012	12 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0505-018	18 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0505-MM500	-	500 mm	Flexible	0.086 in	±6 mm	1.50
415-0505-024	24 in	-	Flexible	0.086 in	±0.25 in	1.50
415-0505-036	36 in	-	Flexible	0.086 in	±0.50 in	1.50
415-0505-M1.0	-	1000 mm	Flexible	0.086 in	±12 mm	1.50

SMP Right Angle Female to SMP Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0511-MM100	-	100 mm	Flexible	0.047 in	±6 mm	1.50
415-0511-006	6 in	-	Flexible	0.047 in	±0.15 in	1.50
415-0511-MM200	-	200 mm	Flexible	0.047 in	±6 mm	1.50
415-0511-MM250	-	250 mm	Flexible	0.047 in	±6 mm	1.50
415-0511-012	12 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0511-018	18 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0511-MM500	-	500 mm	Flexible	0.047 in	±6 mm	1.50
415-0511-024	24 in	-	Flexible	0.047 in	±0.25 in	1.50
415-0511-036	36 in	-	Flexible	0.047 in	±0.50 in	1.50
415-0511-M1.0	-	1000 mm	Flexible	0.047 in	±12 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson


Flexible

SMP Straight Female to SMA Straight Male (26.5 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 26.5 GHz
415-0572-006	6 in	-	Flexible	0.086 in	±0.15 in	1.35
415-0572-012	12 in	-	Flexible	0.086 in	±0.25 in	1.35
415-0572-MM100	-	100 mm	Flexible	0.086 in	±6 mm	1.35
415-0572-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.35

SMPM Straight Female to SMA Straight Male (26.5 GHz)




Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 26.5 GHz
415-0573-006	6 in	-	Flexible	0.086 in	±0.15 in	1.35
415-0573-012	12 in	-	Flexible	0.086 in	±0.25 in	1.35
415-0573-MM100	-	100 mm	Flexible	0.086 in	±6 mm	1.35
415-0573-MM200	-	200 mm	Flexible	0.086 in	±6 mm	1.35

High Performance Cable Assemblies

Johnson


Semi-Rigid

SMPM Straight Female to SMPM Straight Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0524-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0524-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0524-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0524-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0530-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0530-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0530-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0530-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50

SMPM Straight Female to SMPM Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0525-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0525-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0525-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0525-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0531-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0531-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0531-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0531-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson


Semi-Rigid

SMPM Right Angle Female to SMPM Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0526-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0526-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0526-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0526-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0532-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0532-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0532-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0532-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50

SMP Straight Female to SMP Straight Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0500-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0500-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0500-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0500-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0506-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0506-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0506-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0506-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50




+1 507.833.8822
ccsorders@us.cinch.com
cinch.com

High Performance Cable Assemblies

Johnson


Semi-Rigid

SMP Straight Female to SMP Right Angle Female (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0501-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0501-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0501-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0501-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0507-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0507-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0507-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0507-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50

SMP Right Angle Female to SMP Right Angle Female (18 GHz)




Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0502-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0502-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0502-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0502-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0508-006	6 in	-	Semi-Rigid	0.047 in	±0.15 in	1.50
415-0508-012	12 in	-	Semi-Rigid	0.047 in	±0.25 in	1.50
415-0508-MM200	-	200 mm	Semi-Rigid	0.047 in	±6 mm	1.50
415-0508-MM250	-	250mm	Semi-Rigid	0.047 in	±6 mm	1.50

High Performance Cable Assemblies

Semi-Rigid

Johnson

SMP Straight Female to SMA Straight Male (18 GHz)



Part Number	Cable Length		Cable Type	Cable Diameter	Tolerance	VSWR (Max) 18 GHz
415-0520-006	6 in	-	Semi-Rigid	0.086 in	±0.15 in	1.50
415-0520-012	12 in	-	Semi-Rigid	0.086 in	±0.25 in	1.50
415-0520-MM200	-	200 mm	Semi-Rigid	0.086 in	±6 mm	1.50
415-0520-MM250	-	250 mm	Semi-Rigid	0.086 in	±6 mm	1.50